

VARI-FOCAL DAY/NIGHT BULLET CAMERA WITH INFRA-RED LED ILLUMINATORS



- Infra-Red LED Illuminators
- External Lens Adjustment
- Varifocal Lens with Auto Iris
- Weatherproof Housing
- Sunshield
- Mounting Bracket

SPECIFICATIONS

	DC - 12V	AC - 24V
	DSS-3490DN / DSS-3495DN	DSSAC-3490DN / DSSAC-3495DN
Model	DSS-3490DN / DSS-3495DN	DSSAC-3490DN / DSSAC-3495DN
Imager	1/3" Color CCD	1/3" Color CCD
Pixels	512 (H) x 492 (V) NTSC / 768 (H) x 494 (V) NTSC	512 (H) x 492 (V) NTSC / 768 (H) x 494 (V) NTSC
Resolution	400TVL / 480TVL	400TVL / 480TVL
Minimum Illumination	0 Lux (IR LED's ON)	0 Lux (IR LED's ON)
S/N Ratio	48dB	48dB
Shutter Speed	1/60 ~ 1/100,000 Sec	1/60 ~ 1/100,000 Sec
Gamma	0.45	0.45
White Balance	Auto white balance	Auto white balance
Automatic Gain Control	Yes	Yes
Video Output	1Vp-p composite, 75Ohms	1Vp-p composite, 75Ohms
Power Input	Barrel Plug Connector	Bare Wire Leads
Video Output	BNC Connector	BNC Connector
Power Input	DC-12Volt	AC-24 Volt
Current Consumption	7.2 Watts	7.2 Watts
Lens Type	Vari-Focal 4-9mm Auto Iris	Vari-Focal 4-9mm Auto Iris
LED's	18 Individual Super Infra-red LED's	18 Individual Super Infra-red LED's
LED Range	30ft	30ft
Dimensions	2.4" (Dia) x 4.4" (L)	2.4" (Dia) x 4.4" (L)
Operational Temperature	-4 - +122F	-4 - +122F
Housing	Water resistant (Weatherproof)	Water resistant (Weatherproof)
Mounting	1/4" - 20 Thread on rear	1/4" - 20 Thread on rear
Accessories	Sunshield	Sunshield
	Power supply - Weldex WDADP-12/1A	Power supply - Weldex WDADP-24