

FIXED DAY/NIGHT BULLET CAMERA WITH INFRA-RED LED ILLUMINATORS



- Infra-Red LED Illuminators
- Automatic Low Light Sensing
- Weatherproof Housing
- Sunshield
- Mounting Bracket

SPECIFICATIONS

Model	DSS-5407DN	DSS-5457DN
Imager	1/3" Color CCD	1/3" Color CCD
Pixels	512 (H) x 492 (V) NTSC	768 (H) x 494 (V) NTSC
Resolution	400TVL	480TVL
Minimum Illumination	0 Lux (IR LED's ON)	0 Lux (IR LED's ON)
S/N Ratio	48dB	48dB
Shutter Speed	1/60 ~ 1/100,000 Sec	1/60 ~ 1/100,000 Sec
Gamma	0.45 □	0.45 □
White Balance	Auto white balance	Auto white balance
Automatic Gain Control	Yes	Yes
Video Output	1.0Vp-p composite 75Ohms	1.0Vp-p composite 75Ohms
Power Input	Barrel Plug, 2.1mm x 5.5mm Jack Type □	Barrel Plug, 2.1mm x 5.5mm Jack Type □
Video Output	BNC Connector	BNC Connector
Power Input	DC-12Voilt	DC-12Voilt
Current Consumption	250mA Max	250mA Max
Lens Type	Fixed 3.6mm (Other lenses available)	Fixed 3.6mm (Other lenses available)
LED's	12 Individual Super Infra-red LED's	12 Individual Super Infra-red LED's
LED Range	30ft	30ft
Dimensions	1.75" (Dia) x 3" (L)	1.75" (Dia) x 3" (L)
Operational Temperature	-4 - +122F	-4 - +122F
Housing	Water resistant (Weatherproof)	Water resistant (Weatherproof)
Mounting	1/4" - 20 Thread	1/4" - 20 Thread
Accessories	Sunshield Power supply - Weldex WDADP-12/1A	Sunshield Power supply - Weldex WDADP-12/1A